

CCTV CAMERA



MAIN FEATURES

1/3" Sony Super Hi-Res CCD
540 TVL Low Lux 0.3 / F2.0
6 mm CS-Mount Lens
20-Meter IR Range
3-Axis Rotational Internal Brackets

MODEL **CVD4054W**

Dome Infra-Red Camera

Application

This dome camera is designed for ceiling-mount installation. This camera is built with infra-red LEDs and 3D internal bracket. Suitable for indoor use, bracket is not required.

Technical Specifications

Image Sensor	1/3" Sony Hi-Res Color CCD
Resolution	540 TVL
TV System	PAL/NTSC
Pixel Resolutions	752 (H) x 582 (V) PAL
Sync System	Internal
Lens	CS-Mount 6.0 mm
Mini Illumination	0.3 Lux/ F2.0
Scanning System	2:1 Interlace
White balance	Auto
Gain Control Range	Auto 3,200 ~ 10,000 oK
S / N Ratio	> 52 dB
Electronic Shutter	1/50~1/120,000 sec.
Video output	Composite output 1.0V p-p at 75ohm
Gamma Correction	0.45
Operation Temp.	-10 oC ~50 oC
Storage Temp.	-30 oC ~50 oC
Dimensions	100 (D) x 60 (H) mm
Power Consumption	DC12V 130 mA, 300 mA (IR on)



chivar

www.chivar.com



The specification is subject to changes without notice.
Chivar is the registered trade mark of Bestchoice International Co., Ltd.