

CCTV CAMERA



MAIN FEATURES

1/3" CMOS Color
12 PCs 5mm IR LEDs
10 Meter Coverage Range
Ceiling Mount
3.6 mm Lens (Wide Angle)

MODEL **CVD520**

Dome Infra-red Camera

Application

Dome IR camera is good for ceiling mount installation. No bracket is required. It is suitable for indoor use.

Technical Specifications

Image Sensor	1/3" CMOS OV 7910 A Class
Resolution	380 TVL
TV System	PAL 50hz / NTSC 60hz
Sync System	Internal
Mini Illumination	0.8 Lux / 0 Lux, IR ON
Effective Pixels	PAL: 628x582, NTSC: 501x492
Scanning System	2:1 Interlace
White balance	Mode
Gain Control Range	Auto 3,200 ~ 10,000 oK
S / N Ratio	> 40 dB
Electronic Shutter	1/60~1/20,000 sec.
Video output	Composite output 1.0V p-p at 75ohm
Gamma Correction	-
Operation Temp.	-20 oC ~50 oC
Working Place	Indoor
IR Range	12 PCS 5mm LEDs, IR 10 meters / 45o
Lens	3.6mm
Dimensions	92mm(diam) x 80mm
Power Supply	DC12V +/-1V/ 500mA
Power Consumption	<0.4 Watts
Weight	130 grams



chivar

www.chivar.com



The specification is subject to changes without notice.
Chivar is the registered trade mark of Bestchoice International Co., Ltd.