

CCTV CAMERA



MAIN FEATURES

1/3" Sony Color CCD
540 TVL
4-9 mm Vari-Focal CS-Mount Lens
Externally-Adjust Zoom/Focus
30-Meter IR Range

MODEL **CVD955W**

Vandal-Proof Dome Infra-Red Camera

Application

Dome IR camera is designed for ceiling-mount installation. Vandal-proof design makes it suitable for outdoor use. No bracket is required.

Technical Specifications

Image Sensor	1/3" Sony Color CCD
Resolution	540 TVL
TV System	PAL/NTSC
Pixel Resolutions	752 (H) x 582 (V) PAL
Sync System	Internal
Lens	CS-Mount 4-9 mm
Mini Illumination	0 Lux/ IR on
Scanning System	2:1 Interlace
White balance	Auto
Gain Control Range	Auto 3,200 ~ 10,000 oK
S / N Ratio	> 52 dB
Electronic Shutter	1/50~1/120,000 sec.
Video output	Composite output 1.0V p-p at 75ohm
Gamma Correction	0.45
Operation Temp.	-10 oC ~50 oC
Storage Temp.	-30 oC ~50 oC
Dimensions	105 (D) x 60 (H) mm
Power Consumption	DC12V 130 mA, 300 mA (IR on)



chivar

www.chivar.com



The specification is subject to changes without notice.
Chivar is the registered trade mark of Bestchoice International Co., Ltd.