

CCTV HOUSING



(Bracket is Built-in)

MAIN FEATURES

Ceiling-Mouted Housing
Motorized Control (PTZ)
Lens Control (ZFI)
Used with Box Camera

MODEL **CVG807H**

Pan-Tilt-Zoom Housing for Camera

Application

Weatherproof housing for standard camera. It is suitable for outdoor installations. It can stand for heavy rain and dusty areas.

Technical Specifications

Type	Indoor/Outdoor Spherical
Spherical Size	6.5" Inner/ 8.25" Outer
Equipped	PTZ Decoder Blower with sensors
Local Control	Auto/Common/Up/Down/Left/Right Common/Zoom/Focus/Iris
Other Control	RS485
Panning Range	355 °
Tilting Range	90 °
Panning Speed	15 °/sec
Protocol	Multi-protocol :- Pelco D/ Pelco P, etc.
Material	Coated Zinc Housing Plastic Dome
Color	Beige
Camera Power	12 Vdc 500 mA
Decoder Power	24 V ac 2000 mA
Operating Temp	-20° - 50° C
Dimensions	210 (ϕ) x 250 mm
Weight	700 gm
Weather Proof	N.A.



chivar

www.chivar.com



The specification is subject to changes without notice.
Chivar is the registered trade mark of Bestchoice International Co., Ltd.