

CCTV HOUSING



(Bracket is Built-in)

MAIN FEATURES

Weatherproof Housing
Motorized Control (PTZ)
Lens Control (ZFI)
Temperature Control
Used with Box Camera
IP66 Weatherproof

MODEL **CVG809**

Pan-Tilt-Zoom Housing for Camera

Application

Weatherproof housing for standard camera. It is suitable for outdoor installations. It can stand for heavy rain and dusty areas.

Technical Specifications

| | |
|-----------------------|--|
| Type | Indoor/Outdoor Spherical |
| Spherical Size | 8.75" Inner/ 11" Outer |
| Equipped | PTZ Decoder Blower with sensors |
| Local Control | Auto/Common/Up/Down/Left/Right Common/Zoom/Focus/Iris |
| Other Control | RS485 |
| Panning Range | 355 ° |
| Tilting Range | 90 ° |
| Panning Speed | 15 °/sec |
| Protocol | Multi-protocol :- Pelco D/ Pelco P, etc. |
| Material | Aluminum Alloy Bracket Plastic Dome |
| Color | Beige |
| Camera Power | 12 Vdc 500 mA |
| Decoder Power | 24 V ac 2000 mA |
| Operating Temp | -20° - 50° C |
| Dimensions | 280 (ϕ) x 355 x 270 mm |
| Weight | 1,600 gm |
| Weather Proof | IP66 |



chivar

www.chivar.com



The specification is subject to changes without notice.
Chivar is the registered trade mark of Bestchoice International Co., Ltd.