

CCTV CAMERA



(Screw to fix)

MAIN FEATURES

1/3" CMOS Color CCD
6 mm Lens
Built-in Microphone
Flexible Power Sources
Low Power Consumption

MODEL **CVH200**

Miniature Camera

Application

Miniature camera can be used in the areas where users do not want the camera to be explicit.

With flexible power choices and small wattage consumption, it can also be used with 9V battery.

Technical Specifications

| | |
|----------------------------------|----------------------------|
| Color or B/W | Color |
| Sensor | 1/3" CMOS 7131 |
| System of Signal | PAL/CCIR NTSC/EIA |
| Horizontal Resolution | 380TVL |
| Minimum Illumination | 3.0Lux |
| Effective Pixel: | CCIR: 628X582 EIA: 501X492 |
| Auto Exposure Control | 1/60-1/2000 Sec. |
| Scanning System Frequency | CIR: 50HZ. EIA: 60HZ |
| Video output | 1.0Vp-p 75 ohm BNC |
| Audio | 1 RCA |
| S/N Ratio | >40db |
| Power supply | DC 9~12V |
| Power consumption | 12 Vdc 20 mA |
| Dimensions | 17(W) x 17(H) x 22(D) mm |
| Weight | 35 gm |



chivar

www.chivar.com



The specification is subject to changes without notice.
Chivar is the registered trade mark of Bestchoice International Co., Ltd.