

CCTV CAMERA



(Bracket is optional)

MAIN FEATURES

1/3" Sony Color CCD
24 PCs 5mm IR LEDs
20 Meter Coverage Range
IP 66 Weatherproof
3.6 mm (Other Lens is Optional)

MODEL **CVR3059S**

Weatherproof Infra-red Camera

Application

Weatherproof IR camera is applicable to both indoor and outdoor installations. IP66 water and dust resistance makes it worry-free when you need to install in the remote hard-to-reach areas. It can stand for heavy rain and dusty areas.

Technical Specifications

Image Sensor	1/3 Sony High Resolution CCD
Resolution	420 TVL
TV System	PAL/NTSC
Sync System	Internal
Mini Illumination	0 Lux IR ON
Scanning System	2:1 Interlace
White balance	Mode
Gain Control Range	Auto 3200 ~ 10000 oK
S / N Ratio	> 50 dB
Electronic Shutter	1/50~1/120,000 sec.
Video output	Composite output 1.0V p-p at 75ohm
Gamma Correction	0.45
Operation Temp.	-20 oC ~50 oC
Working Place	IP66
IR Range	24 PCS 5mm LEDs, IR 20 meters / 92o
Lens	3.6mm
Dimensions	137mm(L) x diam. 67 mm
Power Supply	DC12V +/-1V/ 500mA



chivar

www.chivar.com



The specification is subject to changes without notice.
Chivar is the registered trade mark of Bestchoice International Co., Ltd.