

CCTV CAMERA



(Bracket is built-in)

MAIN FEATURES

1/3" CMOS Color
11 PCs 5mm IR LEDs
10 Meter Coverage Range
IP 66 Weatherproof
3.6 mm Lens (Wide Angle)

MODEL **CVR410**

Weatherproof Infra-red Camera

Application

Weatherproof IR camera is applicable to both indoor and outdoor installations. IP66 water and dust resistance makes it worry-free when you need to install in the remote hard-to-reach areas. It can stand for heavy rain and dusty areas.

Technical Specifications

Image Sensor	1/3" CMOS OV 7910 A Class
Resolution	380 TVL
TV System	PAL 50hz / NTSC 60hz
Sync System	Internal
Mini Illumination	0 Lux IR ON
Effective Pixels	PAL: 628x582, NTSC: 501x492
Scanning System	2:1 Interlace
White balance	Mode
Gain Control Range	Auto 3200 ~ 10000 oK
S / N Ratio	> 40 dB
Electronic Shutter	1/60~1/20,000 sec.
Video output	Composite output 1.0V p-p at 75ohm
Gamma Correction	-
Operation Temp.	-20 oC ~50 oC
Working Place	IP66
IR Range	11 PCS 5mm LEDs, IR 10 meters / 45o
Lens	3.6mm
Dimensions	45mm(L) x120mm
Power Supply	DC12V +/-1V/ 500mA <0.2 Watts



chivar

www.chivar.com



The specification is subject to changes without notice.
Chivar is the registered trade mark of Bestchoice International Co., Ltd.